



DSMRQR Reflex Red Dot Sight with Quick Detach Mount Instructions

Congratulations, you have purchased one of the finest dot sights available. Special features of ELECTRO-DOT SIGHT include:◆ Tubeless design with 33mm reflex lens aperture provides a wide field of view, suitable for rapid-firing or shooting of moving targets besides normal shooting. ◆Multi-Reticle 4 patterns) or Variable Dot (4 different sizes) are installed.◆Parallax corrected and unlimited eye-relief.◆Allen head screw type windage and elevation click adjustments, with locking screw (see diagram below). ◆Built-in mount(integrated rail) for standard bases, no need to rezero when remounting the dismounted sight.◆Very light weight, waterproof and shockproof.◆Low power consumption for long battery life.

BATTERY:

Your Electro-Dot(E/D) sight is powered by one 3V lithium battery(CR2032 or equivalent). If your reticle grow dim or there is no light, you will need to replace the battery. To install battery, unscrew battery cover and insert new battery + side up, and replace the cover.

MOUNTING:

Your E/D sight includes an integrated rail that fits standard, picatinny and or weaver rails. This is suitable for most applications. Because of unlimited eye-relief with the E/D sight, you should provide at least three inches of clearance between the end of LED & Mirror housing and your eye when shooting. Set the rail onto the base so that the rail claw align with the crosscut grooves. Work the claw into the base until the cross-bolt seats into the groove. Securely tighten the locking screw with a Allen wrench included in the E/D sight.

ZEROING:

Select the reticle you desire by turning the reticle selector knob and set the intensity at the best position for you. With the E/D sight mounted, rest the gun on a solid support and aim at a target 50 to 100 yards(or meter) away. Test shots should be done in the same conditions to achieve maximum accuracy for adjustment, for which the use of firm rest for firing and same type cartridge is recommendable. Each click adjustment moves the point of impact by 1 MOA(approximately 1" at 100vbs, 1/2" at 50 yds.)



SPECIFICATIONS:

Power	Obj aperture	Field of View	Length	Weight
1X	22mmX32mm	15.8m@100m	82mm	195g

OSPREY, A LEADER IN THE WEAPON ACCESSORY INDUSTRY FOR OVER 20 YEARS, CONCENTRATES ON CUTTING-EDGE, NICE PRODUCTS THAT ARE INNOVATIVE IN DESIGN AND PERFORMANCE FOR OUR DISCERNING CUSTOMER BADE. OUR ENTIRE PRODUCT LINE ALSO CARRIES A FULL, NONONSENSE, LIFETIME WARRANTY. OUR CHAMBERABLE BORE SIGHT SYSTEM HAS BEEN TESTED IN LRAQ AND AFGHANISTAN AND APPROVED FOR USE BY THE U.S. MILITARY FOR THE SNIPER ACCESSORY KITS. IT IS SIMPLY THE BEST BORE SIGHT SYSTEM IN THE WORLD, WHICH WE PAINSTAKINGLY DEVELOPED OVER MANY YEARS. BELOW ARE SOME OF THE POINTS WHICH SEPARATE OSPREY FROM ALL THE OTHERS. OUR RIFLE SCOPE LINE IS ASSEMBLED IN CHINA, WHERE WE UTILIZE CHINESE LABLOR BUT NOT CHINESE COMPONENTS. FOR EXAMPLE, THE LENSES USED IN OUR TACTICAL SCOPE FAMILY ARE FROM HOYA OR JAPAN, AND WE IMPORT 3M AND LOC-TITE TWO-PART EPOXIES AND HERMETIC GREASE FROM THE UNITED STATES FOR ALL BONDING APPLICATIONS. 100% OF THE UNITS ARE INSPECTED FOR FOG-PROOFING AND WATER-PROOFING, AND EVERY SCOPE IS TESTED AND WARRANTED FOR SHOCK TO 50BMG PARAMETERS(1000G/0.4-0.8MS). EACH SCOPE IS ALSO SPIN-CENTERED FOR BALANCE AND POSSESSES FULLY, MULTI-COATED GLASS LENSES THROUGHOUT WITH GLASS-ETCHED RETICLES. OUR SCOPES HAVE NOW REACHED SALES OF OVER 100, 000 PLUE UNITS AND DEVOID OF BEING BIAS. WE FEEL IT IS THE BEST SCOPE DOLLAR-FOR-DOLLAR EVER AVAILABLE. ALBEIT WE MAY SEEM TO BE MAKING SOME BOLD AND PRETENTIOUS STATEMENTS, WE FEEL ANYONE WHO PURCHASES OUR SCOPES WILL AGREE. WE WILL ALSO WORK TO CONTINUE IMPROVING AND REDUCING COSTS ON OUR MANY OTHER KEY PRODUCTS, INCLUDING BUT NOT LIMITED TO GREEN LSAERS, TACTICAL LIGHTS, RED LASERS, AND THE MANY OTHER ITEMS WE HAVE PROVIDED IN YEARS PAST. IN CLUDING, WE WOULD LIKE TO THANK ALL OF OUR PAST AND FUTURE CUSTOMERS, AND LOOK FORWARD TO MANY YEARS OF PROVODOMG YOU WITH QUALITY PRODUCTS, AFFORDABLE PRICES, AND THE BEST CUSTOMER SERVICE AND WARRANTY IN THE BUSINESS.

KEITH OLIVER-CEO
RANDY BURKE-PRESIDENT
OSPREY GLOBAL
370 GILMER FERRY ROAD,
BALL GROUND, GA 30107
SALES@MINIOSPREY.COM
PHONE: 678-454-1060
FAX: 678-454-1061

PLS NOTE THAT IF YOU HAVE THE RETURNS OR DEFECTIVE PRODUCTS, PLS SEND THEM TO 2529 REGENCY ROAD, LEXINGTON, KY 40503 SUITE#106.